



梅 USER'S MANUAL

DIGITAL ANALOG CONVERTER (DAC)

Note: Please connect DC power cable before AC power cable. Disconnect the AC power before disconnecting the DC power. Failure to do so could potentially cause damage.



HOLLO AUDIO
RAY

TABLE OF CONTENTS

OVERVIEW	01
SPECIFICATIONS	02
FRONT PANELS	03
OVERSAMPLING MODE	05
CONFIGURATION MODE	05
REAR PANELS	06
REMOTE CONTROL	07
I2S PORT PINOUT	08



OVERVIEW

May, "The Possibility of"

A new generation DAC of fully discrete resistor network (commonly known as R2R).

FEATURES

- The new generation of linear compensation technology solves the accuracy errors caused by resistor tolerance, after compensation, reaching a variance of 0.00005% tolerance accuracy.
- Proprietary anti-jitter technology that provides a full amplitude of anti-jitter without increasing noise floor and other undesirable effects.
- Based on this new generation of technology May “梅” can provide a SINAD of >115dB and a dynamic range of >130dB, which represents the performance limit reached by today's most advanced R2R architecture DAC.
- Using the ultimate performance of PLL+FIFO technology, provides 0.1Hz Third-Order low-pass ability to inhibit jitter. It also uses a high-performance femtosecond VCXO as the PLL clock source. Under the premise of being almost immune to the front-end jitter, it can also lock up to 1.5us-2us @ 1KHz signal with high jitter. (It can lock up to 1.5us-2us @ 1kHz signal with high jitter on the premise of almost being immune front-end jitter).
- Dual Mono DAC L/R channels are independently powered by their own dedicated transformer in the PSU chassis. This provides better channel separation and more accurate sound stage.
- Supports USB and I2S up to DSD1024 and PCM1.536MHz sample rates.
- The USB interface uses proprietary firmware with ultra-low latency, a highly reliable data transmission, ideal USB eye pattern measurements that contributes to 2-4 times higher performance than official firmware.
- Two sets of independent HDMI-I2S input interfaces are provided, and each set of I2S has a four-way independent circuit, as opposed to standard LVDS chip, making I2S clock signals subject to lower interference and lower jitter. In addition, each group of I2S inputs can be configured with specific pinout configuration, making it compatible with most of the HDMI-I2S digital devices on the market.



SPECIFICATIONS

DIGITAL INPUT

COAXIAL1, COAXIAL2, OPTICAL, AES	PCM 44.1-192K (24bit) DSD 64X (DOP)
USB	PCM 44.1K-1.536M (32bit) DSD 64-512X (DOP) DSD 64-1024X (Native)
I2S1, I2S2	PCM 44.1K-1.536M (32bit) DSD 64-1024X

ANALOG OUTPUT

PCM 48K NOS	THD+N 0.00017% @1K(-115dB) DNR 130dB Voltage Output 2.9Vrms (RCA), 5.8Vrms (XLR)
DSD 128X	THD+N 0.00025% @1K(-112dB) DNR 115dB Voltage Output 1.45Vrms (RCA), 2.9Vrms (XLR)

PHYSICAL CHARACTERISTICS

Size (Main Box)	430x300x55mm (W x L x H, Dimensions do not include protruding parts)
Size (Power Chassis)	430x300x55mm (W x L x H, Dimensions do not include protruding parts)
Weight	18kg/39.68lbs



CONFIGURATION

Power Input (configurable, see label on bottom of unit for specified input)	220-230V 50/60Hz - Fuse Type 2A SB 5x20mm
	110-115V 50/60Hz - Fuse Type 4A SB 5x20mm
Power consumption	60W



ACCESSORIES

Included Accessories	AC Power Cable x1
	DC Power Cable x1
	USB Cable x1
	Remote Control x1



FRONT PANELS

01 POWER SUPPLY CHASSIS - FRONT PANEL



02 DAC (MAIN) CHASSIS - FRONT PANEL



BUTTON CONFIGURATION

POWER, DISPLAY MODE / MENU, OVER SAMPLING / ←, SOURCE / →

LEFT OF DISPLAY

POWER (INDICATION LIGHT IS RED WHEN POWERED IN OFF-STATE, AND GREEN WHEN ON)

Press and hold this button for 1 second to switch the power on and off. In the off state, all is power is off except for the standby circuit and red indication light, other circuits of the May "梅" will stop working and stop outputting.

RIGHT OF DISPLAY, 4 BUTTONS FROM LEFT TO RIGHT:

MUTE

In the silent mode, some of the May "梅" output stage circuit turns off. However, the power consumption is essentially unchanged, and will maintain its hot machine state.

DISPLAY MODE / MENU

In normal operation (display) mode, press this button to select whether to turn off the display automatically; in configuration (menu) mode, press this button to select the configuration item.

OVER SAMPLING / ←

In Normal (over-sampling) mode, press this button to select oversampling mode. In configuration mode, press this button to change the configuration mode (left).

SOURCE / →

In Normal mode, press this button to select the digital source. In configuration mode, press this button to change the configuration mode. Select the digital input source, including USB (ground isolated), RCA, BNC, AES, fiber optic, I2S-1 and I2S-2.



OVERSAMPLING MODES

❧ NOS - NO OVERSAMPLING MODE

directly converts the original data. Since digital oversampling can cause time domain distortion such as ringing effects, NOS can avoid these problems. Generally speaking, NOS has a significant impact on other performance indicators, but the May “梅” is designed to maintain good performance in NOS mode.

❧ OS - OVER SAMPLING MODE

Super-sampling the PCM to a higher frequency PCM
oversampling the DSD to a higher frequency DSD
performing a digital to analog conversion.

❧ OS PCM - OVER SAMPLING/PCM MODE

whether it is PCM input or DSD input, always oversample to PCM for digital analog conversion.

❧ OS DSD - OVER SAMPLING DIRECT STREAM DIGITAL MODE

Whether in PCM input or DSD input, super-sampling to DSD mode for digital analog conversion.



CONFIGURATION MODE

How to enter Configuration mode: In shutdown mode (powered off state, red light indicated) press and hold the menu button and power button to enter menu mode. Then press the menu button to select the configuration mode, press the left button or right button to change the configuration mode.

CONFIGURATION MODE OPTIONS (LEFT TO RIGHT SELECTION)

I2S1 FMT

Select from HOLO, ALT1, ALT2, ALT3. Reference I2S Port Pinout for an explanation and the I2S line sequence. (See page 8)

I2S2 FMT

Select from HOLO, ALT1, ALT2, ALT3. Reference I2S Port Pinout for an explanation and the I2S line sequence. (See page 8)

OUT POL

STANDARD, the analog RCA output is normal polarity, balanced XLR output 1-Ground, 2-Hot, 3-cold. REVERSED, the analog RCA output is reverse polarity, balanced XLR output 1-Ground, 2-Cold, 3-Hot.

PLL


Select ON to turn on the PLL function and work with all digital input signals to eliminate jitter. Select OFF to turn off the PLL function.




REAR PANELS

Note please connect DC power before AC power. Similarly, disconnect the AC power before disconnecting the DC power supply. Failure to do so could potentially cause damage.

01 POWER SUPPLY CHASSIS • REAR PANEL




02 DAC (main) - Rear Panel





REMOTE CONTROL




*This is a universal HOLO AUDIO remote. Volume (+/-) is not applicable to the “梅” May DAC as there is no pre-amp built in, will work simultaneously with other HOLO Audio branded products i.e. pre-amps and head-amps.



I2S PORT PINOUT

Using LVDS differential transmission. Physical interface and HDMI consistent, you can use the HDMI cable. But note that the electrical signal transmission is I2S, not conventional HDMI audio and video signals.



Pin	HOLO		ALT1		ALT2		ALT3	
	PCM	DSD	PCM	DSD	PCM	DSD	PCM	DSD
1	I2S_DATA-	DSD_L-	I2S_DATA+	DSD_L+	I2S DATA-	DSD R-	I2S DATA+	DSD_R+
2	GND	GND	GND	GND	GND	GND	GND	GND
3	I2S DATA+	DSD L+	I2S DATA-	DSD L-	I2S DATA+	DSD_R+	I2S DATA-	DSD_R-
4	I2S_BCLK+	DSD BCLK+	I2S BCLK+	DSD BCLK+	I2S BCLK+	DSD BCLK+	I2S BCLK+	DSD BCLK+
5	GND	GND	GND	GND	GND	GND	GND	GND
6	I2S_BCLK-	DSD BCLK-	I2S_BCLK-	DSD_BCLK-	I2S BCLK-	DSD BCLK-	I2S BCLK-	DSD BCLK-
7	I2S_LRCK-	DSD R-	I2S L_RCK+	DSD R+	I2S LRCK-	DSD L-	I2S LRCK+	DSD L+
8	GND	GND	GN D	GND	GND	GND	GND	GND
9	I2S LRCK+	SDR+	I2S LRCK-	DSD R-	I2S LRCK+	DSD L+	I2S LRCK-	DSD L-
10	I2S_MCLK+	DSD_MCLK+	I2S MCLK+	DSD MCLK+	I2S MCLK+	DSD MCL K+	I2S MCLK+	DSD MCLK+
11	GND	GND	GND	GND	GND	GND	GND	GND
12	I2S MCLK-	DSD_MCLK-	I2S_MCLK-	DSD MCLK-	I2S MCLK-	DSD MCLK-	I2S MCL K-	DSD MCLK-
13	NC	NC	NC	NC	NC	NC	NC	NC
14	NC	NC	NC	NC	NC	NC	NC	NC
15	NC	NC	NC	NC	NC	NC	NC	NC
16	RSV	RSV	NC	NC	NC	NC	NC	NC
17	GND	GND	GND	GND	GND	GND	GND	GND
18	NC	NC	NC	NC	NC	NC	NC	NC
19	GND	GND	GND	GND	GND	GND	GND	GND

